

Cascadia

Creating Remote Possibilities™

Dome Camera - Ultra High Resolution
600 TVL (Color) / 650 TVL (B&W)
True Day & Night (ICR) / SDNR
Dual Voltage



C60TS2

Lens Not Included

Model	C60TS2
Image Device	1/3" SONY Super HAD CCD II
Pixels	811 (H) x 508 (V) / 410K Pixels
Scanning System	NTSC / 525 Lines / 2:1 Interlace
Special Features	OSD / True Day & Night (ICR) Cut Filter / Super Digital Noise Reduction (SDNR) Mirror (Horizontal) / Privacy Mask - 4 Zones / Motion Detection - 4 Zones
Horizontal Resolution (TV Lines)	600 TV Lines (Color) / 650 TV Lines (B&W)
Minimum Illumination (Lux)	0.1 Lux (Color) / 0.03 Lux (B&W)
Day/Night Mode	True Day & Night (ICR) Cut Filter
Electronic Shutter Speed	1/60 ~ 1/120,000
Signal to Noise Ratio (S/N)	More than 50dB (AGC Off)
AGC	On/Off
Super BLC / SDNR	Off/Low/Middle/High
White Balance	ATW/Manual/Push
Mirror	Horizontal
Camera Control	RS-485 / Pelco-D
Video Output	Composite (1.0Vp-p) / 75 Ω
Lens Type	Manual Iris / Video Auto Iris / DC Auto Iris
Lens Mount	C/CS
Power Requirements	24 VAC / 12 VDC
Power Consumption	3.6W (300mA/12VDC)
Connectors	Terminal Screws
Operating Temperature	14° ~ 122°F
Storage Temperature	-4° ~ 158°F
Operating Humidity	90% RH (Non-Condensing)
Body Construction / Color	Die Cast Aluminum Long Body Case / Silver
Weight	Approx. 430g
Dimensions (WxHxL)	64mm x 57.6mm x 124.7mm

*Specifications subject to change without notice.



Four Year Warranty

(888) 421-0050 / www.cascadiadvrt.com