

# Cascadia

Creating Remote Possibilities™

**Dome Camera - Ultra High Resolution**  
**600 TVL (Color) / 650 TVL (B&W)**  
**2.8 ~ 10.5mm Varifocal Lens**  
**True Day & Night (ICR) / SDNR**  
**Dual Voltage**  
**3-Axis / Service Video Out**



## D60VTS2

Auto Iris 2.8 ~ 10.5mm  
Varifocal Lens Included

Model	D60VTS2
Image Device	1/3" SONY Super HAD CCD II
Pixels	811 (H) x 508 (V) / 410K Pixels
Scanning System	NTSC / 525 Lines / 2:1 Interlace
Special Features	OSD / True Day & Night (ICR) Cut Filter / Super Digital Noise Reduction (SDNR) Mirror (Horizontal) / Privacy Mask - 4 Zones / Motion Detection - 4 Zones
Horizontal Resolution (TV Lines)	600 TV Lines (Color) / 650 TV Lines (B&W)
Lens	Auto Iris 2.8 ~ 10.5mm Varifocal Lens
Minimum Illumination (Lux)	0.1 Lux (Color) / 0.01 Lux (B&W)
Day/Night Mode	True Day & Night (ICR) Cut Filter
Electronic Shutter Speed	1/60 ~ 1/120,000
Signal to Noise Ratio (S/N)	More than 50dB (AGC Off)
AGC / Flickerless	On/Off
Super BLC / SDNR	Off/Low/Middle/High
White Balance	ATW/Manual/Push
Video Output	Composite (1.0Vp-p) / 75 Ω
3-Axis / Service Video Out	Yes
Power Requirements	24 VAC / 12 VDC
Power Consumption	2.2W / (183mA/12VDC)
Connectors	Power (Red) / Video (Yellow)
Operating Temperature	14° ~ 122°F
Storage Temperature	-4° ~ 158°F
Operating Humidity	90% RH (Non-Condensing)
Body Construction / Color	ABS / White
Weight	Approx. 366g
Dimensions (WxH)	123mm x 95mm

\*Specifications subject to change without notice.



**Four Year Warranty**

(888) 421-0050 / [www.cascadiadvrt.com](http://www.cascadiadvrt.com)