

# Cascadia

Creating Remote Possibilities™



**XM24016T**

**IVM Ready / 240 IPS / w/ Two Way Voice  
16 Channel Video / 1 Channel Audio  
Digital Video Recorder Transmitter**

Model	XM24016T
IVM Ready	Yes
Video Format	NTSC / PAL
Video Output	YUV 4:2:2 / Composite (1 Channel Switched)
Image Capture Size	352x240 / 720x240 / 720x480
Compressed Image Size	352x240 = Average 2.5Kb / 720x480 = Average 10Kb
Display (Screen Divisions)	1, 4, 6, 9, 10, 13, 16
Display Speed	240 Images Per Second (IPS) System Wide
Recording Speed	352x240 = Up to 240 IPS Total / 720x480 = Up to 150 IPS Total
Transmission Speed	Up to 25 IPS Per Channel
Transmission Modes	PSTN / ISDN / TCP/IP
WEB Software Included	Yes
Remote Software Included	Yes (Open Licenses)
Alarm Inputs / Relay Outputs	4 Inputs and 4 Outputs (Optional)
PTZ Controls	Yes (RS-232)
System Watch Dog	Yes
Switched Monitor Output	Yes (Dwell Time Adjustable)
Case	Tower Case
Dimensions HxWxD (in)	16.5 x 7.75 x 18.3
Weight	Approx. 35 lbs
Operating System	Windows 2000
System Configuration	PIV 2.4Ghz or Greater
Communication Hardware	Network (Modem Optional)
Main System Memory	256 MB RAM
Graphics Card	32 MB
Main System Hard Drive	10 GB or Greater
Maximum Internal Drives	7
Removable Storage	CDRW / 1.44 Floppy

**XM-Series  
XM24016T (16 Channel)**

***Two Year Warranty***  
*\*Specifications subject to change without notice.*

**(888) 421-0050 / [www.cascadiadvrt.com](http://www.cascadiadvrt.com)**