

Cascadia

Creating Remote Possibilities™



XM304T

**IVM Ready / 30 IPS / w/ Two Way Voice
4 Channel Video / 1 Channel Audio
Digital Video Recorder Transmitter**

Model	XM304T
IVM Ready	Yes
Video Format	NTSC / PAL
Video Output	YUV 4:2:2 / Composite (1 Channel Switched)
Image Capture Size	352x240
Compressed Image Size	352x240 = Average 2.5Kb / Image
Display (Screen Divisions)	1, 4
Display Speed	30 Images Per Second (IPS) System Wide
Recording Speed	352x240 = Up to 30 IPS Total
Transmission Speed	Up to 25 IPS Per Channel
Transmission Modes	PSTN / ISDN / TCP/IP
WEB Software Included	Yes
Remote Software Included	Yes (Open Licenses)
Alarm Inputs / Relay Outputs	4 Inputs and 4 Outputs (Optional)
PTZ Controls	Yes (RS-232)
System Watch Dog	Yes
Switched Monitor Output	Yes (Dwell Time Adjustable)
Case	Tower Case
Dimensions HxWxD (in)	16.5 x 7.75 x 18.3
Weight	Approx. 35 lbs
Operating System	Windows 2000
System Configuration	PIV 2.4Ghz or Greater
Communication Hardware	Network (Modem Optional)
Main System Memory	256 MB RAM
Graphics Card	32 MB
Maximum Internal Drives	7
Removable Storage	CDRW / 1.44 Floppy

**XM-Series
XM304T (4 Channel)**

Two Year Warranty

**Specifications subject to change without notice.*

(888) 421-0050 / www.cascadiadvrt.com